

Part no. AL-1052-18612

12-24 V, white



Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	1,2
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	Innenraumbeleuchtung
Beam angle [°]	
Colour Temperature (K)	5000
Others	
Ingress protection	IP67
Resistivity	
Standards	
Electromagnetic Compatibility	
Transient spike protection	

Dimensions

Mounting

Mounting type	Einbau
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch-Stecker (DT04-2P)
Mating connector	Deutsch-Stecker (DT06-2S)
Reverse polarity protection	1
Black wire	Masse
Red wire	Innenleuchte

Part no. AL-1052-18612

Others

Material (Housing)	Polycarbonat
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Silber
Color (Mount)	
Color (Diffusing lens)	Weiß

Beam pattern

Variants

AL-1052-18612	12-24 V, weiß
---------------	---------------

Accessories