

Part no. AL-2371-41211

12-48 V, with switch and 60 minute timer

Specifications

Voltage range (V), nominal	12-48
Voltage range (V), functional	
Power consumption (W)	1.12-3.36
Load capacity	
Temperature range (°C)	-40 to 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	5000
Others	
Ingress protection	IP67
Resistivity	
Standards	UL
Electromagnetic Compatibility	
Transient spike protection	

Dimensions

Mounting

Mounting type	Flat mounting (2 screws, M4)
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch plug (DT04-2P)
Mating connector	Deutsch plug (DT06-2S)
Reverse polarity protection	1
Black wire	Masse
Red wire	Innenleuchte

Part no. AL-2371-41211

Others

Material (Housing)	Polycarbonat
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

Beam pattern

Variants

AL-2371-41211	12-48 V, mit Schalter und 60-Minuten-Timer
---------------	--

Accessories