

LED-Einbau-Arbeitsscheinwerfer Modell 6043

Part no. AS-1068-1224



12-24 V, 700 lm, w/ tail light (red)

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	7,2 (Arbeitsscheinw.); 1,31 (Schlussl.)
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	700
Brightness (cd)	
Brightness (lx)	
Performance class	bis 1000 lm eff.
Beam pattern/lens	Geländeausleuchtung, mit Rücklicht
Beam angle [°]	
Colour Temperature (K)	5000
Others	
Ingress protection	IP67
Resistivity	
Standards	FMVSS (108), SAE (J585)
Electromagnetic Compatibility	
Transient spike protection	150 V @ 1 Hz-10 Pulse

Dimensions

Mounting

Mounting type	Einbau
Installation dimensions/diameter [mm]	113
Installation depth [mm]	22
Connector	Kabel
Mating connector	
Reverse polarity protection	1
Black wire	Masse
Red wire	Rücklicht
White wire	Arbeitsscheinwerfer

LED-Einbau-Arbeitsscheinwerfer Modell 6043

Part no. AS-1068-12240

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Grau
Color (Mount)	
Color (Diffusing lens)	Klar

Beam pattern

Variants

AS-1068-12240	12-24 V, mit Rücklicht (rot)
---------------	------------------------------

Accessories