

Part no. AS-1195-90494



4 modules, 12-24 V, 2,640 lm, flood

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	96
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	2640
Brightness (cd)	
Brightness (lx)	
Performance class	1000 to 3000 lm eff.
Beam pattern/lens	Geländeausleuchtung
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP67
Resistivity	
Standards	
Electromagnetic Compatibility	SAE (J1113)
Transient spike protection	

Part no. AS-1195-90494

Dimensions

Mounting

Mounting type	Spec. mounting bracket
Installation dimensions/diameter [mm]	102,87 mm x 727,71 mm
Installation depth [mm]	93.22
Connector	
Mating connector	
Reverse polarity protection	1

Part no. AS-1195-90494

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	

Beam pattern

Variants

AS-1195-90494	4 Module, 12-24 V, 2640 lm, Geländeausleuchtung
---------------	---

Accessories