

Part no. **AS-1771-78121**



12 V, 460 lm, trap, 1 light

## Specifications

<b>Voltage range (V), nominal</b>	12
<b>Voltage range (V), functional</b>	9-16
<b>Power consumption (W)</b>	14,4
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-40 bis 65
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	1242
<b>Brightness (effective lm)</b>	460
<b>Brightness (cd)</b>	1380
<b>Brightness (lx)</b>	
<b>Performance class</b>	bis 1000 lm eff.
<b>Beam pattern/lens</b>	Nahfeldausleuchtung
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	IP67 & IP69K
<b>Resistivity</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Einbau
<b>Installation dimensions/diameter [mm]</b>	115,1x72,9
<b>Installation depth [mm]</b>	61,83
<b>Connector</b>	Delphi MP280-2M (12059450-B)
<b>Mating connector</b>	Delphi MP280-2F (12124819)
<b>Reverse polarity protection</b>	1

# LED-Einbau-Arbeitsscheinwerfer Modell 785

Part no. **AS-1771-78121**

## Others

Material (Housing)	Nylon 66
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

## Variants

AS-1771-78121	12 V, 460 lm, Nahfeldausleuchtung, 1 Stück
AS-1776-78122	12 V, 460 lm, Nahfeldausleuchtung, 2 Stück

## Accessories