

**Part no. AS-2105-52111**



24 V, flood, dual white

## Specifications

<b>Voltage range (V), nominal</b>	24
<b>Voltage range (V), functional</b>	16-32
<b>Power consumption (W)</b>	78
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-40 bis 65
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	9000 / 7500 (Kaltweiß/Warmweiß)
<b>Brightness (effective lm)</b>	3464 / 3390 (Kaltweiß/Warmweiß)
<b>Brightness (cd)</b>	4488 / 4508 (Kaltweiß/Warmweiß)
<b>Brightness (lx)</b>	
<b>Performance class</b>	über 3000 lm eff.
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	5000 / 2800
<b>Others</b>	
<b>Ingress protection</b>	IP69K
<b>Resistivity</b>	
<b>Standards</b>	
<b>Electromagnetic Compatibility</b>	ECE (Reg. 10)
<b>Transient spike protection</b>	330 V @ 1 Hz-100 Pulse

## Dimensions

## Mounting

<b>Mounting type</b>	Universalhalterung, M10-1,5x25
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>White wire</b>	Kaltweiß
<b>Green wire</b>	Warmweiß

**Part no. AS-2105-52111**

## Others

<b>Material (Housing)</b>	Aluminium
<b>Material (Diffusing lens)</b>	Polycarbonat
<b>Color (Housing)</b>	Gelb
<b>Color (Mount)</b>	
<b>Color (Diffusing lens)</b>	Klar

## Beam pattern

## Variants

<b>AS-2105-52111</b>	24 V, Geländeausleuchtung, Dual-Weiß
----------------------	--------------------------------------

## Accessories