

Part no. AS-2105-52111



24 V, flood, dual white

Specifications

Voltage range (V), nominal	24
Voltage range (V), functional	16-32
Power consumption (W)	78
Load capacity	
Temperature range (°C)	-40 to 65
Brightness	
Brightness (raw lm)	9000 / 7500 (Kaltweiß/Warmweiß)
Brightness (effective lm)	3464 / 3390 (Kaltweiß/Warmweiß)
Brightness (cd)	4488 / 4508 (Kaltweiß/Warmweiß)
Brightness (lx)	
Performance class	more than 3000 lm eff.
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	5000 / 2800
Others	
Ingress protection	IP69K
Resistivity	
Standards	
Electromagnetic Compatibility	ECE (Reg. 10)
Transient spike protection	330 V @ 1 Hz-100 pulses

Dimensions

Mounting

Mounting type	Universal mount, M10-1.5x25
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	1
Black wire	Masse
White wire	Kaltweiß
Green wire	Warmweiß

Part no. AS-2105-52111

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Gelb
Color (Mount)	
Color (Diffusing lens)	Klar

Beam pattern

Variants

AS-2105-52111	24 V, Geländeausleuchtung, Dual-Weiß
----------------------	--------------------------------------

Accessories