

## Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	9-30
Power consumption (W)	44.16-52.56
Load capacity	
Temperature range (°C)	-40 to 65
Brightness	
Brightness (raw lm)	6372
Brightness (effective lm)	3800
Brightness (cd)	5839
Brightness (lx)	
Performance class	more than 3000 lm eff.
Beam pattern/lens	Geländeausleuchtung
Beam angle [°]	
Colour Temperature (K)	5050
Others	
Ingress protection	IP67 & IP69K
Resistivity	
Standards	
Electromagnetic Compatibility	ECE (Reg. 10)
Transient spike protection	330 V @ 1 Hz-100 pulses

## Dimensions



## Mounting

<b>Mounting type</b>	Universal mount, 5/16"
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	Deutsch plug (DT04-2P)
<b>Mating connector</b>	Deutsch plug (DT06-2S)
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>Red wire</b>	Arbeitsscheinwerfer

Part no. AS-2172-89111

## Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

## Beam pattern

## Variants

AS-2172-89111	12-24 V, Geländeausleuchtung
---------------	------------------------------

## Accessories

AS-2113-79111	Modell 792 12-24 V, Geländeausleuchtung, Einbau
AS-2093-79111	Modell 792 12-24 V, Geländeausleuchtung, Aufbau
AS-2185-89111	Modell 893 12-24 V, breite Geländeausleuchtung
AS-2348-89111	Modell 894 12-24 V, Geländeausleuchtung
AS-2268-79141	Modell 795 12-24 V, Geländeausleuchtung, mit Blinker