

LED-Einbau-Arbeitsscheinwerfer Modell 6040

Part no. AS-874-60402



12 V, 770 lm, trapezoid beam, glass lens

Specifications

| | |
|--------------------------------------|---------------------|
| Voltage range (V), nominal | 12 |
| Voltage range (V), functional | 10-15 |
| Power consumption (W) | 24 |
| Load capacity | |
| Temperature range (°C) | -40 bis 65 |
| Brightness | |
| Brightness (raw lm) | |
| Brightness (effective lm) | 770 |
| Brightness (cd) | |
| Brightness (lx) | |
| Performance class | bis 1000 lm eff. |
| Beam pattern/lens | Nahfeldausleuchtung |
| Beam angle [°] | |
| Colour Temperature (K) | 5000 |
| Others | |
| Ingress protection | IP66 |
| Resistivity | |

Dimensions

Mounting

| | |
|--|---------------|
| Mounting type | Einbau |
| Installation dimensions/diameter [mm] | 112,90, PAR36 |
| Installation depth [mm] | |
| Connector | Steckkontakte |
| Mating connector | |
| Reverse polarity protection | 1 |

LED-Einbau-Arbeitsscheinwerfer Modell 6040

Part no. AS-874-60402

Others

| | |
|----------------------------------|-----------|
| Material (Housing) | Aluminium |
| Material (Diffusing lens) | Glas |
| Color (Housing) | Grau |
| Color (Mount) | |
| Color (Diffusing lens) | Klar |

Variants

| | |
|---------------------|--|
| AS-831-52471 | 12-48 V, 1070 lm, Nahfeldausleuchtung, Polycarbonat-Streuscheibe |
| AS-832-54081 | 12-48 V, 1070 lm, Geländeausleuchtung, Polycarbonat-Streuscheibe |
| AS-874-60402 | 12 V, 770 lm, Nahfeldausleuchtung, Glas-Streuscheibe |

Accessories