

Part no. BL-1479-37525



12 V, amber

Specifications

Voltage range (V), nominal	12
Voltage range (V), functional	9-16
Power consumption (W)	4,8
Load capacity	
Temperature range (°C)	-30 bis 50
Brightness	SAE Kl. I
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Dimensions

Mounting

Mounting type	Flachmontage, 2 Schrauben
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Kabel
Mating connector	
Reverse polarity protection	1
Red wire	Blitzleuchte
Yellow wire	Moduswahl
Green wire	Masse
Blue wire	Synchronisierung

Part no. BL-1479-37525

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Acryl
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

Variants

BL-1462-37523	24 V, blau
BL-1463-37524	24 V, weiß
BL-1479-37525	12 V, orange
BL-1481-34527	12 V, rot

Accessories