

Part no. BL-1556-30521



12-24 V, amber, ECE road approval (Reg. 65),
Class I, 12-24 V, orange, ECE-Straßenzulassung
(Reg. 65), Class I, 3SA

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	10-30
Power consumption (W)	
Load capacity	
Temperature range (°C)	-40 to 55
Brightness	ECE Reg. 65 Cl. I
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Frequency, revolutions (Hz, rpm, fpm)	
Others	8 different strobe pattern
Ingress protection	IP67
Resistivity	
Standards	
Electromagnetic Compatibility	ECE (Reg. 10)
Transient spike protection	

Dimensions

Mounting

Mounting type	Flat mounting (2 screws)
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bare wire leads
Mating connector	
Reverse polarity protection	1
Socket	

Part no. BL-1556-30521

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Weiß

Beam pattern

Variants

BL-1556-30521	12-24 V, orange, ECE-Straßenzulassung (Reg. 65), Class I, 3SA
----------------------	---

Accessories