

Part no. BL-1830-37521



12-24 V, blue, ECE road approval (Reg. 65)

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	
Load capacity	0.9
Temperature range (°C)	-30 to 50
Brightness	SAE Cl. I
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	21 diff. strobe pattern
Ingress protection	IP67
Resistivity	

Dimensions

Mounting

Mounting type	Surface mount, adhesive, spec. mounting bracket
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bare wire leads
Mating connector	
Reverse polarity protection	0
Black wire	Masse
Red wire	Blitzleuchte
Yellow wire	Synchronisierung
Blue wire	Moduswahl

Part no. BL-1830-37521

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

Variants

BL-1829-37520	12-24 V, orange, ECE-Straßenzulassung (Reg. 65)
BL-1830-37521	12-24 V, blau, ECE-Straßenzulassung (Reg. 65)
BL-1831-37523	12-24 V, weiß, ECE-Straßenzulassung (Reg. 65)
BL-1833-37525	12-24 V, rot, ECE-Straßenzulassung (Reg. 65)

Accessories