

Part no. BL-2111-31511



10-30 V, amber, ECE road approval (Reg. 65),
with magnetic mount and vehicle charger cable

Specifications

Voltage range (V), nominal	10-30
Voltage range (V), functional	
Power consumption (W)	36
Load capacity	
Temperature range (°C)	-40 bis 70
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP67
Resistivity	

Part no. BL-2111-31511

Dimensions

Mounting

Mounting type	Magnethalter
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bordspannungsstecker
Mating connector	
Reverse polarity protection	1

Part no. BL-2111-31511

Others

Material (Housing)	
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Orange

Variants

BL-2110-31511	10-30 V, orange, ECE-Straßenzulassung (Reg. 65), Rohrmontage
BL-2111-31511	10-30 V, orange, ECE-Straßenzulassung (Reg. 65), mit Kfz.-Ladekabel und Magnetfuß

Accessories