

Part no. **BL-2239-71511**



12-24 V, green

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	9-32
<b>Power consumption (W)</b>	26,2
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-30 bis 50
<b>Brightness</b>	SAE Kl. I
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	

Dimensions

Mounting

Mounting type	Saugnapf, Magnet
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bordspannungsstecker
Mating connector	
Reverse polarity protection	1

**Part no. BL-2239-71511**

## Others

<b>Material (Housing)</b>	Aluminium
<b>Material (Diffusing lens)</b>	Polycarbonat
<b>Color (Housing)</b>	Silber
<b>Color (Mount)</b>	
<b>Color (Diffusing lens)</b>	Rot

## Variants

<b>BL-2239-71511</b>	12-24 V, grün
----------------------	---------------

## Accessories