

12-32 V, blue, ECE road approval (Reg. 65), 3 bolt

Specifications

Voltage range (V), nominal	12-32
Voltage range (V), functional	
Power consumption (W)	66
Load capacity	
Temperature range (°C)	-30 to 50
Brightness	SAE Cl. I
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	12 versch. Blitzmuster
Beam angle [°]	
Colour Temperature (K)	
Frequency, revolutions (Hz, rpm, fpm)	
Others	
Ingress protection	IP69K
Resistivity	
Standards	ECE (Reg. 65), CISPR 25-3
Electromagnetic Compatibility	ECE (Reg. 10)
Transient spike protection	

Dimensions

Mounting

Mounting type	Flat mounting (3 screws)
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	1
Socket	

Part no. **BL-2343-51511**

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	Klar

Beam pattern

Variants

BL-2343-51511	12-32 V, blau, ECE-Straßenzulassung (Reg. 65), 3 Schrauben
----------------------	--

Accessories