

**Part no. BL-2370-40511**

12-24 V, amber, 3-point mounting

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	
<b>Power consumption (W)</b>	3.8
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Frequency, revolutions (Hz, rpm, fpm)</b>	
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	
<b>Standards</b>	ECE (Reg. 65)
<b>Electromagnetic Compatibility</b>	ECE (Reg. 10)
<b>Transient spike protection</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Flat mounting (3 screws)
<b>Installation dimensions/diameter [mm]</b>	91,5
<b>Installation depth [mm]</b>	
<b>Connector</b>	Bare leads
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	1
<b>Socket</b>	

**Part no. BL-2370-40511**

## Others

Material (Housing)	
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Grau
Color (Mount)	
Color (Diffusing lens)	Orange

## Beam pattern

## Variants

<b>BL-2370-40511</b>	12-24 V, Orange, 3-Punkt-Montage
----------------------	----------------------------------

## Accessories