Blitzleuchte XTP6

Part no. BL-2373-60521

12-24 V, white/white, 6 LED

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	10.8
Load capacity	1
Temperature range (°C)	-40 to 65
Brightness	SAE Cl. I
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Frequency, revolutions (Hz, rpm, fpm)	30 versch. Blitzmuster
Others	
Ingress protection	IP67 & IP69K
Resistivity	
Standards	
Electromagnetic Compatibility	ECE (Reg. 10)
Transient spike protection	

Bei der Pulvermühle 7a | 22453 Hamburg
+49 40 303300-0 | info@jfuehr.com | www.jfuehr.com

J. FÜHR

Part no. BL-2373-60521

Dimensions



Mounting

Mounting type	Flat mounting (2 screws)
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bare leads
Mating connector	
Reverse polarity protection	1
Socket	
Black wire	Masse
Red wire	Blitzleuchte
Yellow wire	Synchronisierung
White wire	Blitzleuchte
Blue wire	Moduswahl

Bei der Pulvermühle 7a | 22453 Hamburg
+49 40 303300-0 | info@jfuehr.com | www.jfuehr.com

Part no. BL-2373-60521

Others

Material (Housing)	Polycarbonat
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

Beam pattern

Variants

BL-2373-60521	12-24 V, weiß/weiß, 6 LEDs

Accessories

Bei der Pulvermühle 7a | 22453 Hamburg
+49 40 303300-0 | info@jfuehr.com | www.jfuehr.com

J. FÜHR