

Part no. BL-384-7101


11-110 V, amber, roof-mounting



Specifications

Voltage range (V), nominal	12-80
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	SAE Kl. III
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP65
Resistivity	

Dimensions



Mounting

Mounting type	Dachmontage (3 Schrauben)
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Kabel
Mating connector	
Reverse polarity protection	0
Black wire	Masse
Red wire	Blitzleuchte

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Orange

Variants

BL-384-71010	12-80 V, orange, Dachmontage
BL-2034-64651	12-80 V, orange, Magnethalter und KfZ-Kabel

Accessories

BL-303-00018	Blendschutz-Lichthaube schwarz, für Blitzleuchte 6410/6465
BL-265-00017	Ersatzlichthaube für Blitzleuchte 6410/6465, rot
BL-264-00016	Ersatzlichthaube für Blitzleuchte 6410/6465, grün
BL-263-00015	Ersatzlichthaube für Blitzleuchte 6410/6465, weiß/farblos
BL-262-00014	Ersatzlichthaube für Blitzleuchte 6410/6465, blau
BL-094-00002	Ersatzlichthaube für Blitzleuchte 6410/6465, orange
BL-781-31280	Halteblech für Blitzleuchte 6410/6465
BL-120-00008	Schutzkorb 6410 für Blitzleuchte 6410/6465, Metall