

Part no. FS-1742-86351



12 V, high and low beam, front position light,
ECE road approval (Reg. 50, 113)

Specifications

Voltage range (V), nominal	12
Voltage range (V), functional	9-16
Power consumption (W)	20 (Abblendl.), 32 (Fernl.), 1,6 (Standl.)
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	925 (Abblendl.), 1620 (Fernl.)
Brightness (effective lm)	500 (Abblendl.), 850 (Fernl.)
Brightness (cd)	12110 (Abblendl.), 41000 (Fernl.)
Brightness (lx)	
Performance class	
Beam pattern/lens	Abblend- und Fernlicht, Standlicht
Beam angle [°]	
Colour Temperature (K)	5000
Others	
Ingress protection	IP67
Resistivity	

Dimensions

Mounting

Mounting type	Einbau
Installation dimensions/diameter [mm]	143,5
Installation depth [mm]	
Connector	H4-Stecker
Mating connector	H4 (AMP 172515-2)
Reverse polarity protection	1
Black wire	Masse
Red wire	Standlicht
Yellow wire	Abblendlicht
White wire	Fernlicht

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	Chrom
Color (Diffusing lens)	Klar

Variants

FS-1742-86351	12 V, Abblend- und Fernlicht, Standlicht, ECE-Straßenzulassung (Reg. 50, 113)
FS-1920-86351	12 V, Abblend- und Fernlicht, Standlicht, ECE-Straßenzulassung (Reg. 50, 113), Dark Chrome

Accessories

FS-1042-87030	Montagering 8630/8631 für LED-Fahrscheinwerfer Modell 8630 und 8631, schwarz
FS-1048-86302	Montagering für LED-Fahrscheinwerfer Modell 8630 und 8631, schwarz, nur äußerer Ring
FS-1457-87391	Scheinwerfertopf für LED-Fahrscheinwerfer Modell 8630 und 8631, schwarz, 1-Punkt-Montage, inkl. O-Ring & Tülle