

12-24 V, low beam, ECE road approval (Reg. 112)

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	9-32
<b>Power consumption (W)</b>	25,2-24,0
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-40 bis 65
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	2830
<b>Brightness (effective lm)</b>	782
<b>Brightness (cd)</b>	29.800
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	5000
<b>Others</b>	
<b>Ingress protection</b>	IP69K
<b>Resistivity</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Universalhalterung, 1/2"
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	H4 (AMP #172615-2)
<b>Mating connector</b>	LH AMP #172795-1, RH AMP #172796-1
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>Yellow wire</b>	Abblendlicht
<b>White wire</b>	Abblendlicht

# LED-Fahrscheinwerfer Modell 8801 Evolution 2

**Part no. FS-2134-88311**

## Others

<b>Material (Housing)</b>	Aluminium
<b>Material (Diffusing lens)</b>	Polycarbonat
<b>Color (Housing)</b>	Schwarz
<b>Color (Mount)</b>	Chrom
<b>Color (Diffusing lens)</b>	Klar

## Variants

<b>FS-2134-88311</b>	12-24 V, Abblendlicht, ECE-Straßenzulassung (Reg. 112)
<b>FS-2135-88321</b>	12-24 V, Fernlicht, ECE-Straßenzulassung (Reg. 112)

## Accessories