

12-24 V, auxiliary high beam, ECE road approval

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	9-30
Power consumption (W)	60-64.8
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	9800
Brightness (effective lm)	1650
Brightness (cd)	150000
Brightness (lx)	
Performance class	
Beam pattern/lens	Fernlicht
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP67
Resistivity	

Dimensions

Mounting

Mounting type	Spec. mounting bracket
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch plug (DT04-2P)
Mating connector	Deutsch plug (DT06-2S)
Reverse polarity protection	1
Black wire	Masse
Red wire	Fernlicht

Part no. FS-2332-99321

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

Variants

FS-2332-99321	12-24 V, Zusatz-Fernlicht, ECE-Straßenzulassung
FS-2333-90321	12-24 V, Zusatz-Fernlicht, mit beheizter Frontscheibe, ECE-Straßenzulassung

Accessories