

LED-Fahrtrichtungsanzeiger Modell 245

Part no. PL-1217-24502



12-24 V, ECE road approval (Reg. 6), amber lens

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	4,2-3
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Brightness (reference index)	
Performance class	
Beam pattern/lens	Fahrtrichtungsanzeiger
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP67
Resistivity	
Standards	ECE (Reg. 6), SAE (J575, J588)
Electromagnetic Compatibility	
Transient spike protection	

Dimensions

Mounting

Mounting type	Einbau
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch-Stecker (DT04-2P)
Mating connector	Deutsch-Stecker (DT06-2S)
Reverse polarity protection	1
Socket	
Black wire	Masse
Red wire	Fahrtrichtungsanzeiger

LED-Fahrtrichtungsanzeiger Modell 245

Part no. PL-1217-24502

Others

Material (Housing)	ABS-Kunststoff
Material (Diffusing lens)	Acryl
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Orange

Beam pattern

Variants

PL-1217-24502	12-24 V, ECE-Straßenzulassung (Reg. 6), orangefarbene Streuscheibe
---------------	--

Accessories