

Part no. RM-210-15231



For rail diameter from 1.25-3.2 cm (0.5-1.25 in.),
1.5 in. ball (size C), single U-bolt

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-210-15231	Für Rohrdurchmesser 1,25-3,2 cm (0,5-1,25 Zoll), 1,5-Zoll-Kugel (Größe C), Einzelbügel RAM-231ZU
RM-211-15271	Für Rohrdurchmesser 3,2-4,7 cm (1,25-1,875 Zoll), 1,5-Zoll-Kugel (Größe C) RAM-271U-12
RM-212-15271	Für Rohrdurchmesser 5,1-6,35 cm (2-2,5 Zoll), 1,5.Zoll-Kugel (Größe C) RAM-271U-2
RM-217-15235	für Rohrdurchmesser 1,9-3,1 cm (0,75-1,25 Zoll), 1,5-Zoll-Kugel, Doppelbügel RAM-235U
RM-220-15235	für Rohrdurchmesser 3,1-3,8 cm (1,25-1,5 Zoll), 1,5-Zoll-Kugel (Größe C), Doppelbügel RAM-235-1U
RM-234-15231	für Rohrdurchmesser von 1,25-2,54 cm (0,5-1 Zoll), 1,5-Zoll-Kugel (Größe C), Einzelbügel RAM-231U

Accessories