

Part no. RM-228-10408



For rail diameter 0.95-1.59 cm (0.375-0.625 in.), 1 in. ball (size B)

## Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

## Dimensions

## Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

**Part no. RM-228-10408**

## Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

## Variants

<b>RM-209-10231</b>	Für Rohrdurchmesser 1,25-3,1 cm (0,5-1,25), 1-Zoll-Kugel (Größe B), Einzelbügel, schwarz RAM-B-231ZU
<b>RM-219-10235</b>	für Rohrdurchmesser 1,9-3,1 cm (0,75-1,25 Zoll), 1-Zoll-Kugel (Größe B), Doppelbügel RAM-B-235U
<b>RM-222-10407</b>	für Rohrdurchmesser 1,9-2,5 cm (0,75 -1 Zoll), 1-Zoll-Kugel (Größe B), RAM-B-408-75-1U
<b>RM-228-10408</b>	für Rohrdurchmesser 0,95-1,59 cm, 1-Zoll-Kugel (Größe B) RAM-B-408-37-62U

## Accessories