

Part no. RM-236-22271



for rail diameter 5.1-6.35 cm (2-2.5 in.), 2.25 in.
ball (size D)

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-236-22271

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-218-22235	für Rohrdurchmesser 3,2-3,8 cm (1,25-1,5 Zoll), 2,25-Zoll-Kugel (Größe D) RAM-D-235-1U
RM-226-22235	für Rohrdurchmesser 1,9-3,2 cm (0,75-1,25 Zoll), 2,25-Zoll-Kugel (Größe D) RAM-D-235U
RM-235-22271	Für Rohrdurchmesser 3,2-4,7 cm (1,25-1,875 Zoll), 2,25-Zoll-Kugel (Größe D) RAM-D-271U-12
RM-236-22271	für Rohrdurchmesser 5,1-6,35 cm (2-2,5 Zoll), 2,25-Zoll-Kugel (Größe D) RAM-D-271U-2

Accessories