

# Tough-Claw™ Klammerbasis, 1 Zoll

**Part no. RM-300-104**



For rail diameter 1,6-3,8 cm (0,625-1,5 in.) or  
edges up to 2,9 cm (1,14 in.), 1 in. ball (size B) -  
RAP-B-400U

## Specifications

<b>Voltage range (V), nominal</b>	
<b>Voltage range (V), functional</b>	
<b>Power consumption (W)</b>	
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	

**Part no. RM-300-10400**

## Dimensions

## Mounting

<b>Mounting type</b>	
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	0

# Tough-Claw™ Klammerbasis, 1 Zoll

**Part no. RM-300-10400**

## Others

<b>Material (Housing)</b>	
<b>Material (Diffusing lens)</b>	
<b>Color (Housing)</b>	
<b>Color (Mount)</b>	
<b>Color (Diffusing lens)</b>	

## Variants

<b>RM-300-10400</b>	Für Rohrdurchmesser 1,6-3,8 cm (0,625-1,5 Zoll) oder Kanten bis 2,9 cm (1,14 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-400U
<b>RM-301-10401</b>	Für Rohrdurchmesser 2,5-5,6 cm (1-2,25 Zoll) oder Kanten bis 5,7 cm (2,2 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-401U
<b>RM-302-10404</b>	Für Rohrdurchmesser 2,5-4,75 cm (1-1,875 Zoll) oder Kanten bis 4 cm (1,6 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-404U

## Accessories

<b>RM-501-10201</b>	Verbindungsstück, 1 Zoll 7,6 cm (3 Zoll), für 1-Zoll-Kugel (Größe B) RAM-B-201U
---------------------	---