

Part no. RM-611-00235



Rail base, for rail diameter 3,2-3,8 cm (1,25-1,5 in.), 2,25 in. ball (size DC), double U-bolt, with double socket arm, 16,7 cm, and round base, 9.35 cm, AMPS

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	

Part no. RM-611-00235

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-611-00235

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-606-00201	VESA-Basis, 9,2x9,2 cm (VESA75), 2,25-Zoll-Kugel (Größe D), mit Verbindungsstück, 8,1 cm, mit VESA-Basis, 9,2x9,2 cm (VESA75)
RM-611-00235	Bügelbasis, für Rohrdurchmesser 3,2-3,8 cm (1,25-1,5 Zoll), 2,25-Zoll-Kugel (Größe D), mit Verbindungsstück, 16,7 cm, und runder Basis, 9,35 cm

Accessories