

Part no. RM-862-0032



10-28 V (input), 5-12 V (output), 5-24 W, 3 A max.

Specifications

Voltage range (V), nominal	10-28
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Part no. RM-862-00320

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-862-00320

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-827-00900	20-60 V RAM-GDS-CHARGE-V9U
RM-840-00100	10-32 V
RM-855-00710	10-30 V, mit mUSB-Kabel
RM-862-00320	10-28 V (Eingang), 5-12 V (Ausgang), 5-24 W, 3 A max.
RM-863-00711	10-30 V (Eingang), 5-9 V (Ausgang), 2,5 A max., mit USB-A-2.0-Kabel
RM-864-002800	30-64 V (Eingang), 5-9 V (Ausgang), 2,5 A max., mit USB-A-Buchse

Accessories