

Part no. RW-1541-60722



12-24 V, 77-97 dB, multi frequency, Smart Alarm

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	8,4
Load capacity	
Temperature range (°C)	-40 to 85
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP66
Resistivity	

Part no. RW-1541-60722

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Bare wire leads
Mating connector	
Reverse polarity protection	0
Black wire	Masse
Red wire	Rückfahrwarner

Part no. RW-1541-60722

Others

Material (Housing)	Stahl, glasfaserverstärktes Nylon
Material (Diffusing lens)	
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	

Variants

RW-320-30931	12-48 V, 82-102 dB, Smart Alarm
RW-1541-60722	12-24 V, 77-97 dB, Multi-Frequenz, Smart Alarm

Accessories