

**Part no. RW-1699-68873**



12-24 V, 112 dB, multi frequency

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	9-32
<b>Power consumption (W)</b>	21,3
<b>Load capacity</b>	1,5
<b>Temperature range (°C)</b>	-40 bis 85
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	IP66
<b>Resistivity</b>	

**Part no. RW-1699-68873**

## Dimensions

## Mounting

<b>Mounting type</b>	
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	Kabel
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	0
<b>Black wire</b>	Masse
<b>Red wire</b>	Rückfahrwarner

**Part no. RW-1699-68873**

## Others

<b>Material (Housing)</b>	Nylon (mit Glasfaser verstärkt)
<b>Material (Diffusing lens)</b>	
<b>Color (Housing)</b>	Schwarz
<b>Color (Mount)</b>	
<b>Color (Diffusing lens)</b>	

## Variants

<b>RW-800-80721</b>	12-24 V, 97-112 dB, Typ 1060
<b>RW-1699-68873</b>	12-24 V, 112 dB, Multi-Frequenz

## Accessories