

Part no. TL-1216-24501



12-24 V, stop light and tail light, red, ECE road approval (reg. 7)

Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	
Power consumption (W)	2-2,3
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	Schluss- und Bremslicht
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	IP67
Resistivity	

Dimensions

Mounting

Mounting type	Einbau
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch-Stecker (DT04-2P)
Mating connector	Deutsch-Stecker (DT06-2S)
Reverse polarity protection	1
Black wire	Masse
Red wire	Schlusslicht
Brown wire	Bremslicht

Part no. TL-1216-24501

Others

Material (Housing)	ABS-Kunststoff
Material (Diffusing lens)	Acryl
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Rot

Variants

TL-1000-24503	12-24 V, Rückfahrscheinwerfer, weiß, ECE-Straßenzulassung (Reg. 23)
TL-1216-24501	12-24 V, Brems- und Schlusslicht, rot, ECE-Straßenzulassung (Reg. 7)

Accessories