

Part no. TL-1562-27441

for LED tail light model 279



Specifications

|                               |  |
|-------------------------------|--|
| Voltage range (V), nominal    |  |
| Voltage range (V), functional |  |
| Power consumption (W)         |  |
| Load capacity                 |  |
| Temperature range (°C)        |  |
| Brightness                    |  |
| Brightness (raw lm)           |  |
| Brightness (effective lm)     |  |
| Brightness (cd)               |  |
| Brightness (lx)               |  |
| Brightness (reference index)  |  |
| Performance class             |  |
| Beam pattern/lens             |  |
| Beam angle [°]                |  |
| Colour Temperature (K)        |  |
| Others                        |  |
| Ingress protection            |  |
| Resistivity                   |  |
| Standards                     |  |
| Electromagnetic Compatibility |  |
| Transient spike protection    |  |

Part no. TL-1562-27441

Dimensions

Mounting

|                                       |   |
|---------------------------------------|---|
| Mounting type                         |   |
| Installation dimensions/diameter [mm] |   |
| Installation depth [mm]               |   |
| Connector                             |   |
| Mating connector                      |   |
| Reverse polarity protection           | 0 |
| Socket                                |   |

Part no. TL-1562-27441

Others

|                           |  |
|---------------------------|--|
| Material (Housing)        |  |
| Material (Diffusing lens) |  |
| Color (Housing)           |  |
| Color (Mount)             |  |
| Color (Diffusing lens)    |  |

Beam pattern

Variants

|               |                                |
|---------------|--------------------------------|
| TL-1562-27441 | für LED-Rückleuchte Modell 279 |
|---------------|--------------------------------|

Accessories