

Part no. WL-2168-52511

12-24 V, blue line



Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	9-33
Power consumption (W)	39,6-26,6
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	Für den Blitzmodus müssen sowohl Schwarz und Weiß mit Masse verbunden werden!
Ingress protection	IP67 / IP69K
Resistivity	

Dimensions

Mounting

Mounting type	Universalhalterung, M8
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	Deutsch-Stecker (DT04-3P)
Mating connector	Deutsch-Stecker (DT06-3S)
Reverse polarity protection	1
Black wire	Masse
Yellow wire	Warnlinie
White wire	Blitz-Modus

Part no. WL-2168-52511

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

WL-2096-52551	12-24 V, rote Linie
WL-2138-52511	12-24 V, grüne Linie
WL-2168-52511	12-24 V, blaue Linie

Accessories